



F1001

Coriolis Mass Flowmeter

Model Selection

F1001-Series

Example F1001-025AN2COMEX2P1

F1001	Size	Connection	PN	Struct.	Ex	Power	Output	Accuracy	Description
1/2"	015								Size
1"	025								
1 1/2"	040								
2"	050								
3"	080								
4"	100								
6"	150								
8"	200								
12"	300								
ANSI		AN							Flange Standard
DIN		DI							
JIS		JS							
Others		OF							
1.6MPa			1						Max. Working Pressure
2.5MPa			2						
4.0MPa			3						
6.4MPa			4						
Compact Version (-50°C ~ +125°C)				COM					Housing
Remote Version (-50°C ~ +200°C)				REM					
Non-Explosion					NX				Approval
Explosion proof					EX				
DC						1			Power Supply
AC						2			
4 to 20mA/Pulse							P		Signal Output
RS485+Pulse+4 to 20mA							R		
Hart+Pulse+4 to 20mA							H		
±0.1%								1	Accuracy
±0.2%								2	
±0.5%								5	

※ The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

GPE Inc.

Factory Address:
 9-17 Libella Court, Essex County, Newark, NJ 07105
 Tel: +1(646)619-1289 Fax: +1(212)400-7201
www.gpeus.com sales@gpeus.com